



WESTFALIA
Metallschlauchtechnik

Am Schwanenweiher 1
57271 Hilchenbach

Telefon (02733) 283-100
Telefax (02733) 283-310

info-wsh@westfalia-group.com
www.westfalia-group.com



Exhaust Hose – Type DSS

Design:

Round, double interlocked special profile

Material:

Order NO. 822 Stainless steel strip,
heat resistance up to 650 °C

Special materials on request

Characteristics:

The special winding technique leads to nearly perfect gas tightness and flexibility. The hose provides optimal tensile strength and resistance to crushing, impact and mechanical stress. It also guarantees perfect absorption of axial, lateral and angular vibrations and is able to smooth out fitting tolerances. Highest gas-tightness and flexibility as well as additional protection against outer pollution.

Application:

Used as decoupling element in exhaust systems of truck producers.

Delivery:

Fixed lengths with end fittings according to customers' requirements respectively production lengths.

How to order:

S61XXX – XXX
Order NO., see data sheet Material

Technische Ausführung

Bestell-Nr.	Abmessung			Gewicht gestaucht gemessen +/- 10% [kg/m]
	Innen-Ø [mm]	Außen-Ø [mm]	Toleranz +/- [mm]	
S61077	77,0	81,5	0,6	2,920
S61080	80,0	84,5	0,6	3,030
S61085	85,0	89,5	0,6	3,220
S61090	90,0	94,5	0,6	3,400
S61100	100,0	104,5	0,8	3,770
S61102	102,5	107,0	0,8	3,850
S61106	106,5	111,0	0,8	4,010
S61110	110,0	114,5	0,8	4,140
S61115	115,0	119,5	0,8	4,320
S61120	120,0	124,5	0,8	4,510
S61125	125,0	129,5	0,8	4,690
S61127	127,5	132,0	0,8	4,780
S61128	128,0	132,5	0,8	4,800
S61130	130,0	134,5	0,8	4,880
S61140	140,0	144,5	1,0	5,250
S61145	145,0	149,5	1,0	5,430
S61150	150,0	154,5	1,0	5,610

Technische Parameter gemäß Kundenspezifikation.
 Technische Änderungen vorbehalten.